



FAST ROPE SET UP

1 Papworth Business Park | Stirling Way
Papworth | Cambs CB23 3WA

Tel: +44 1480 832200
info@supply999.com

The following is intended as a guide to the set up of our fast rope kit.

REQUIREMENTS 2 Stowaway ladders with step ladder links fitted.
Fast rope attachment set.

SAFETY NOTES

1. Only use ladders and kit that have a current annual test certificate.
2. Visually inspect the ladders and kit before use and replace damaged items.
3. This kit should only be setup and used by officers trained in its use.
4. Only use the kit as setup below and for fast or slow rope descent.
5. DO NOT use the setup as lifting apparatus.
6. Never leave the setup unattended whilst it is in use.
7. Do not exceed the safe working load of 275kg (maximum 2 officers).
8. Dynamic loadings can increase the load on the setup and should be minimised.
9. Horizontal loadings can adversely affect the stability of the set



SETUP

10. Erect the Stowaway ladders in the step ladder mode as shown in fig1.
11. Place the fast rope end frames on the top of each ladder as shown in fig 2.
12. Slide the cross beam, with the lug on the underside, into the end frames and lock it in place using the pins provided as shown in fig 2.
13. Attach the rope to the lug and then finalise the position of the setup ensuring that the feet of the ladders are on a flat and level plane.



If we can be of further assistance please contact us or our agent.

